

Projektor multimedialny Sanyo PLC-XF46E

Â Cena wynajmu: 1200,00 PLN PROMOCJA WYNAJMU Resolution XGA (1024 x 768) Brightness 12,000 ANSI Lumens (4-lamp mode) / 6,000 ANSI Lumens (2-lamp mode)

Cena wynajmu: 1200,00 PLNÂ

Resolution XGA (1024 x 768)

Brightness 12,000 ANSI Lumens (4-lamp mode) / 6,000 ANSI Lumens (2-lamp mode)

Uniformity 90% (corner to corner)

LCD Panel System 1.8â TFT polysilicon type x 3

Number of Pixels 2,359,296 (786,432 x 3)

Contrast Ratio 1300:1 (full on/off)

Projection Lens Lens Sold Separately

Image Size Dependent on Lens

Aspect Ratio 4:3

Throw Distance Dependent on Lens

Zoom/Focus Dependent on Lens

Throw Ratio Dependent on Lens

Zoom Ratio Dependent on Lens

Power Lens Shift Up/Down Ratio 10:0 â 0:10 or 8:1 â 1:8

Left/Right Ratio 3:2 â 2:3 or 1:1 (Dependent on Lens)

Digital Keystone Correction +/- 30Â° (Vertical)

Projection Lamp 300W UHP x 4

Scanning Frequency H Sync: 15-120kHz, V Sync: 50-120Hz

Dot Clock 230MHz

Color System PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43

Computer Compatibility UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA, MAC

Voltage 120V AC 16A Max, 50//60 Hz (auto sense/select)

BTU Rating 5797

dB Rating 51.0

Power Consumption 1700W

Dimensions (WxHxD) 22.9âx9.9âx30.8â (not including Adjustable Feet)

Net Weight 80.5 lbs.

User Maintenance Clean air filters, replace lamp assembly

Â

Detachable Input Panels

Â

POA-MD18DVI - Digital Visual Interface (DVI-I w/HDCP) â□□Left & Right

Audio (RCA x 2) â□□Control (Min DIN 8-pin)

POA-MD16VD1 - RGB & Component (5-BNC) â□□Left & Right Audio (RCA x 2) â□□Control (Min DIN 8-pin)

POA-MD03VD2A - Composite & Y/C (2-BNC) â□□S-Video (Mini DIN 4-pin)

â□□Left & Right Audio (RCA x 2)

POA-MD04VGA - VGA (D-Sub 15) â□□Left & Right Audio (RCA x 2) â□□Control (Min DIN 8-pin)